

Dotronix DOT-X 29MV Specification



- Maximum Resolution: 1024 x 768 (XGA), 60 Hz
- 27" Viewable Pure Flat Screen Tube
- 0.68 mm Dot Pitch
- 8514A, VESA (XGA, SVGA, VGA) Compatibility
- HDTV Ready: 480i, 480p, 1080i, 720p
- R8-232 Remote Control
- 2 Digits Up to 99 ID Addressable Settings for RS-232 Connection and IR Remote Control
- Enable/Disable the Front Panel Function Operation.
- Auto Degauss Function
- Auto Shift Function
- On Screen Display and IR Remote Control
- 1 x D-Sub 15 Pin PC Input Port
- 1 x D-Sub 15 Pin PC Output Port
- Power Supply: 100 - 240 VAC Universal, 50/60 Hz
- Power Consumption: 210 W Maximum: Standby: 10 W
- Dimensions: 617 (24.3") W x 489 (19.3") H x 495 (19.5") D
- Net Weight: 50 KG (111 Lbs.)
- Gross Weight: 56 KG (124 Lbs.)
- TV/Video Converter (Option)

Videowall Dimensions - Requires Outside Engineering for Stackable Videowall Applications

W x H	1x1	1x2	1x3	2x2	2x3	3x3	4x4
Width	616 (24.3")	616 (24.3")	616 (24.3")	1235 (48.6")	1235 (48.6")	1854 (73.0")	2474 (97.4")
Height	487 (19.2")	977 (38.5")	1467 (57.8")	977 (38.5")	1467 (57.8")	1467 (57.8")	1955 (77.0")
Depth	500 (19.7")						
Power Consumption	210	420	630	840	1260	1890	3360
Net Weight	50 (110LB.)	100 (221LB.)	150 (331LB.)	200 (441LB.)	300 (662LB.)	450 (993LB.)	800 (1764LB.)

www.dotronix.com



www.dotronix.com

160 First Street S.E., St. Paul, MN 55112-7894, USA 800-720-7218 651-633-1742 Fax 651-633-1065